



**Utförande:** Lackerad aluminium. Vit, svart, rödorange RAL 040 50 70 alt. grå RAL 000 50 00 alt. beige/paper RAL 1011. Bländskydd av opal akryl. Skrämen är vridbar.

**LED info:** Systemeffekt 17W. Armaturlumen 1700LM. Korrelerad färgtemperatur 3000K. Färgtolerans SDCM 3. Färgåtergivning RA 80.

**Montage:** Pendlad i 2 m vajer.

**Anslutning:** 2,5 m kabel med stickpropp, vid HFF utan stickpropp.

**Design:** TAF 2014.

W	FÄRG/FINISH	ART.
LED 1700LM	Vit/White	8315-3-01
LED 1700LM	Vit/White	8315-3-01HFF
LED 1700LM	Svart/Black	8315-3-06
LED 1700LM	Svart/Black	8315-3-06HFF
LED 1700LM	Rödorange/Redorange	8315-3-07
LED 1700LM	Rödorange/Redorange	8315-3-07HFF
LED 1700LM	Beige/Beige	8315-3-49
LED 1700LM	Beige/Beige	8315-3-49HFF
LED 1700LM	Grå/Grey	8315-3-95
LED 1700LM	Grå/Grey	8315-3-95HFF

HFF = Dimmbart/Dimmable DALI, SwitchDim, DSI.

**Finish:** Painted aluminium. White, black, redorange RAL 040 50 70 or grey RAL 000 50 00. Diffuser in opal acrylic. The shade is turnable.

**LED info:** System power: 17W. Luminaire Luminous Flux: 1700LM. CCT 3000K. SDCM 3. CRI 80.

**Installation:** In ceiling, 2 meter wire.

**Connection:** 2,5 m cable with plug, when HFF without plug.

**Design:** TAF 2014



